

quest



a rewarding statement of your success



QUEST Midback, Highback, Executive and Integral visitor chair.



Arm options include a height-adjustable, Scorpio or Flexi arm with leather arm pads

Unique, ergonomic and flexible, the Quest is a significant chair of functional beauty

- + A distinctive geometric back design creates angles which support the body in all the right places;
- + generously sized, the executive work chair features a lightweight aluminium frame shell with an upholstery or netting option;
- + the Quest allows freedom of movement - encouraging you to vary your posture - keeping you comfortable and productive;
- + a wide seat and backrest have enough space for the hips and thighs improving circulation to the users legs, healthy comfort and balanced body support;
- + adjustable backrests - to 5 set positions - allow sitters to lean back and rest their necks and
- + designed and produced in South Africa by Seating.



specs

quest



8960 QUEST UPH. EXECUTIVE
D 700 x W 700 x H 1320 mm



8950 QUEST UPH. HIGHBACK
D 700 x W 700 x H 1230 mm



8940 QUEST UPH. MIDBACK
D 700 x W 700 x H 1130 mm



8910 QUEST VISITOR A/C OR S/C
D 600 x W 580 x H 990 mm



8920 QUEST INTEGRAL VISITOR
D 600 x W 580 x H 990 mm

detail

①	backrest	Available in upholstered or netting backrest versions. The backrest design is defined by ergonomic recommendations and conforms naturally to the user's contours (BS 3044 standard). The upholstered backrest's inner metal frame is manufactured from a solid 19 mm steel-round covered with moulded polyurethane foam (65 shaw hardness factor with a reaction time of 250N per cm ³). The netting's backrest metal frame is manufactured from 25,4 mm x 2,5 mm steel tubing. The backrest is finished by a structurally-enhancing curved chrome backbar.
②	armrest	<ul style="list-style-type: none"> The Poly arm comes standard. Scorpio, Flexi, 4D, 2D height- adjustable and other arm options are also available. The 4D height-adjustable arm allows the user to adjust the arm height by 100 mm at 25 mm increments. The arm pad may be adjusted in 30° increments up to 90°, with two inward and two outward settings to give elbow support with computer or other related tasks. The fixed arm is manufactured from an injection-moulded polypropylene with a glass fibre filler and contains no PVC.
③	seat	Injection-moulded polypropylene seat pan, ergonomically designed to distribute pressure loads across the entire seat surface. The seat pan has been engineered to carry a maximum static load of up to 140 kg. The seat foam is a 60 mm thick CFC-free polyurethane-moulded foam piece. The foam specification is shaw hardness of 45 compression strength and 67 kg cubic meter density. The foam is non-flammable and in accordance with FMVSS 302 automotive standards.
④	mechanism	Synchronized 'point effect' mechanism with 100 mm backrest offset. The mechanism locks in 5 predetermined positions or point to point contact (follow me mode), with backrest 'return prevention' safety function. The synchronous movement of the seat and backrest allows a tilt ratio of 1:2, seat 11° and 22° on the backrest. The body weight tension control has a variable range of 40-130 kg in accordance with BIFMA standards.
⑤	gaslift	The seat height can be adjusted within a 130 mm range by means of a class 4-type gas cylinder – housed in a 50,8 mm x 2 mm steel tube. It is designed with shock absorbing effects to enhance comfort and minimise the chances of spinal injury when sitting down. Optional plastic bellow cover is available.
⑥	base	Standard 700 mm nylon injection-moulded 5-star base with reinforced steel inner ring and lattice construction. A 5-star base with castors allow for easy movement, while the user's feet rest firmly on the floor. Optional chrome 5-star die-cast aluminium base available.
⑦	castors	Heavy duty castors with steel pin – 65 mm diameter. The pin insert is an off-set load bearing type to ensure quick alignment in any direction, giving total manoeuvrability.
⑧	upholstery	Upholstered version: can be upholstered in a fabric, synthetic/genuine leather on backrests and seats. Netting version: 3D netting on the back and synthetic/genuine leather on seats. No netting Executive option available.
	frame	The Visitor chair's sleigh frame is manufactured according to SABS standards. The tubing is 25,4 mm diameter x 2,5 mm wall thickness. The frame comes standard in a silver epoxy finish – with optional colours or chrome – and has been designed to withstand above normal loading without distortion or breakage.
	warranty	<ul style="list-style-type: none"> 7 year warranty on all workmanship and manufactured components based on our recommended usage (an 8 hour shift per day) 24/7 available on request. Please also refer to our sales and repair terms document.
	standards + certification	<ul style="list-style-type: none"> ISO 9001 (design and manufacturing) • ISO 18001 (health and safety) ISO 14001 (environmental management) EN 1335-1 (dimensioning of furniture) • EN 1335-2 (product safety and testing)



Please note all fabric, foam and wooden components, can be flammable.